

3652RK

Creative Touch 3 Series 65" Interactive Flat Panel Display





- Create, connect and collaborate effortlessly with Whiteboard Ready-to-use whiteboard featuring built-in annotation tools
- Advanced touch technology Pen and finger recognition for a seamless experience
- Designed for hybrid learning Teach and collaborate from separate locations in real-time
- Safe and secure viewing experience Anti-glare, anti-fingerprint, low blue light and flicker free TUV certified panel

Robust collaboration, extensive connectivity options and a value-focused design. Combining the latest technology and packed with everything a classroom or business requires, the Creative Touch 3 Series delivers all the functionalities and processing power needed to create, educate and collaborate.

Easily access the front-facing ports for HDMI and USB connectivity. For wireless connectivity, Display Share allows up to four users to share contents at the same time from their Windows, iOS, macOS, Chrome or Android device.

In order to let teachers can now work on their lesson plans from home and instantly bring them to any classroom, our Whiteboard includes Google Classroom with single sign-on (SSO) design, teachers can quickly sync with Google Classroom bringing the benefits of paperless sharing and digital collaboration to the classroom. Furthermore, the easy-to-use IFPDs also make lessons more fun with built-in collaboration tools such as Vote, where teachers are able to collect valuable feedback instantly.

Remotely manage your IFPDs, projectors, LED displays and more. Set alerts, schedule tasks or settings and broadcast announcements.

Optoma's Management Suite (OMS)[™] solution is perfect for easy management and control from any location for all your compatible Optoma devices.

Specifications

·	
Display	Directions IED
Back light	Direct type LED
Size (diagonal)	65"
Resolution	3840 x 2160 (UHD 4K)
Brightness	400
Contrast ratio	5,000:1
/iewing angle	178°
Response time	8ms
ife	50,000 hours
peaker count	2
/atts per speaker	20W
ilass	4 mm Tempered Glass with Anti Glare + Anti Fingerprint
mbient light sensor	Yes
ouch resolution	32768 x 32768
hysical spec	
imensions (W x D x H)	1640 x 1036 x 207
all-hanging screw spec	M8*25mm
ESA holes	600x400
the box	Power Cord
	Remote Control
	Quick Start Guide USB Cable
	HDMI Cable
	Writing Pen x 2
	*
onnections	Inputs 3 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x S/PDIF,
	3 x USB 2.0, 2 x USB 3.0, 1 x USB-C, 1 x RJ45, 1 x
	DisplayPort, 1 x Mic 3.5mm
	Outputs 1 x HDMI 2.0, 1 x Audio 3.5mm, 1 x RJ45
	Control 2 x USB Touchport, 1 x RS232
zel size (top)	17.70mm
zel size (bottom)	45.70mm
zel size (left)	17.70mm
ezel size (right)	17.70mm
perating conditions	20% ~ 93% RH
perating temperature (min)	-10°C
perating temperature (max)	45°C
et weight	39 kg
ross weight	50 kg
ouch system	~
vstem	Windows10/Windows11/Linux/Mac (1 Touch point
	only)/Android/Chrome
uch accuracy	<1.00mm
uch point	Up to 20 points touch
uch tool	Finger, Passive infrared pen
en/finger detection	Yes
ower	
ower supply	AC 100-240V, 50/60 Hz
ower consumption (standby)	0.5W
ower consumption (max)	300W
peration System	
stem version	Android 13.0
	Quad-core
20	Dual-core
AM	4GB
torage	32GB 17 Janaruageau Arabia, Czach, Danish, Dutch, English, Franch
SD / display languages	17 languages: Arabic, Czech, Danish, Dutch, English, French, German, Italian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),
	Turkish

Copyright © 2024, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 07112024092606

